

BUKTI KORESPONDENSI

ARTIKEL JURNAL NASIONAL TERAKREDITASI (SINTA - 3)

Judul Artikel : FP Growth Based Consumer Purchase Patterns for Inventory Optimization in Perishable MSME Supply Chains

Jurnal : EDUMATIC Jurnal Pendidikan Informatika
<https://e-journal.hamzanwadi.ac.id/index.php/edumatic>

Penulis : Afifah Aulia Rahman¹, Firman Noor Hasan^{2*}

No.	Perihal	Tanggal
1.	Bukti konfirmasi submit artikel dan artikel yang di submit	04 Juli 2026
2.	Bukti konfirmasi review dan hasil review	14 Juli 2026
3.	Bukti konfirmasi submit review, respon kepada reviewer, dan artikel yang di-resubmit	15 Juli 2026
4.	Bukti Letter of Acceptance (LoA)	20 Juli 2026

**1. Bukti konfirmasi submit artikel dan
artikel yang di submit
(04 Juli 2026)**

Workflow Publication

Submission Review Copyediting Production

Submission Files

Search

212663	Template Edu_Alifah Aulia Rahman.docx	July 4, 2026	Article Text
212664	Cek - Similarity (12%).pdf	July 4, 2026	Other

Download All Files

Pre-Review Discussions

Add discussion

Name	From	Last Reply	Replies	Closed
No Items				

Consumer Purchasing Pattern Analysis Using the FP-Growth Algorithm for Inventory Availability in MSMEs

Afifah Aulia Rahman¹, Firman Noor Hasan^{2*},

^{1,2} Universitas Muhammadiyah Prof. Dr. Hamka, Indonesia

* Corresponding author: Firman Noor Hasan, Universitas Muhammadiyah Prof. Dr. Hamka, Indonesia
✉ firman.noorhasan@uhamka.ac.id

Copyright: © 2026 by the authors

Received: xx xx xxxx | Revised: xx xx xxxx | Accepted: xx xx xxxx | Published: xx xx xxxx

Abstract

Inventory management in fruit and vegetable distribution businesses faces challenges due to the perishable nature of products and fluctuations in consumer demand. Suboptimal inventory management can lead to overstock or stock shortages, while sales transaction data are often underutilized in decision-making. At Induk Buah & Sayur (IBS), sales and inventory records are still managed using Microsoft Excel, limiting the identification of consumer purchasing patterns. This study aimed to analyze consumer purchasing patterns using the Frequent Pattern Growth (FP-Growth) algorithm to support inventory management. The study applied the Knowledge Discovery in Databases (KDD) methodology, including data collection, preprocessing, data transformation, frequent itemset generation, association rule mining, and evaluation using support, confidence, and lift ratio. The analysis conducted with RapidMiner, produced association rules with a confidence level above 80% and a lift ratio of more than 1. This indicates a significant positive relationship between products frequently purchased by customers. The results demonstrate that the FP-Growth algorithm effectively identifies consumer purchasing patterns to support inventory planning, optimize stock availability, reduce the risk of over.

Keywords: *FP-Growth, Knowledge Discovery in Databases, consumer purchasing patterns, association rules, inventory management.*

To cite this article: Author. (20XX). Title. *Edumatic: Jurnal Pendidikan Informatika*, X(X), XX-XX

INTRODUCTION

Swift progress in information technology has changed numerous facets of life, such as business management and enhancing public services in regional libraries (Nenat et al., 2025). In the digital age, the retail and food sectors encounter heightened competition, rendering consumer preference analysis essential for sustaining business operations (Junaedi et al., 2024). A significant amount of information from sales transaction data is merely kept as operational records without being transformed into strategic insights for the organization (Afriyani & Ali, 2023). Leveraging historical transaction data is essential for crafting marketing strategies, enhancing inventory control, and reducing losses from impaired products (Pratiwi et al., 2023).



Numerous research efforts indicate that transaction data serves as a vital resource for organizations and can support strategic business decision-making when examined with suitable data mining approaches (Musdalifah & Jananto, 2022; Putra et al., 2024). In the food industry, applying the FP-Growth algorithm to analyze customer buying habits enables business owners to customize promotions and menu options, greatly enhancing sales and operational efficiency. Analyzing retail cosmetics sales data enables companies to create tailored product packages as a component of a focused marketing strategy.

A key method in data mining for handling extensive transaction data is association rules, which aim to identify connections between combinations of item (Afriyani & Ali, 2023). The FP-Growth algorithm is a popular approach known for its efficiency in generating frequent item sets through an FP-Tree structure, avoiding the need for a complicated set of candidate items. This approach has shown great success in creating particular guidelines from sales data for inventory forecasting. In contrast to traditional algorithms like Apriori, FP-Growth outperforms in memory utilization and processing speed when handling large datasets. Research utilizing bakery sales data indicates that FP-Growth uses considerably less memory (0.08 MiB) compared to Apriori (45.36 MiB) (Hery & Widjaja, 2024). The scalability benefit arises from FP-Growth's direct utilization of the FP-Tree structure to locate frequent item sets and completely omits candidate generation, a phase that frequently leads to the slowdown of the Apriori algorithm as the number of item combinations rises. Previous comparative studies indicate that FP-Growth produces a higher quantity of association rules with stronger rule strength compared to Apriori, thus making it more advantageous for aiding decision-making in sales tactics (Musdalifah & Jananto, 2022). The execution of this algorithm is based on assessing the minimum support threshold, minimum confidence level, and lift ratio to ascertain the robustness of consumer buying behaviors (Pratiwi et al., 2023). The scalability of FP-Growth enables its application in different industries beyond retail, including mining 10 million blockchain address categories to discover patterns and anomalies in network behavior (Lenus, 2025). And analyzing more than 8,000 Solid-State Drive (SSD) error records to enhance customer service strategies and quality control in production (Chang et al., 2021)

Earlier studies have effectively implemented the FP-Growth algorithm across different domains. In the retail industry, FP-Growth has been employed to discover patterns and connections in consumer behavior, allowing management to create better inventory policies and enhance marketing strategies, similar to what occurred at Heron Store. In the fashion retail industry, a study on the G.I.B Store in Cimahi effectively employed FP-Growth on 1,025 online and offline transactions during 2023 to uncover important product relationships. The research revealed a 77.91% confidence level of correlation between specific premium clothing products, directly reinforcing boosted sales, promotional coherence, and enhanced inventory control. A separate retail analysis of 371 transactions from distribution outlets under different minimum support conditions (1%, 2%, and 3%) revealed that FP-Growth consistently produces accurate association rules, aiding business owners in creating successful up-selling and cross-selling approaches. Comparable achievements occurred in the culinary sector, where analyzing 960 transaction records from a juice and soup establishment uncovered consumer preference patterns, thereby enhancing sales and product placement strategies. At the MSME level, like Cafe Over Limit, FP-Growth examines numerous transactions to suggest suitable menu packages for clients, thus accelerating ordering processes (Hasan et al., 2023). A study at Ayam Geprek Purwokerto employed FP-Growth to determine the frequent product combinations such as white rice usually combined with chicken breast and iced tea—allowing the store to optimize

inventory management, stimulate impulse purchases through strategic initiatives, and design appealing combo packages. In the processed food manufacturing industry, especially at PT Kusno Baso, FP-Growth is implemented in the CRISP-DM framework to create cross-selling strategies aimed at resolving product accumulation and sales reductions caused by unsold stock (Prasetyo & Hasugian, 2023). The use of FP-Growth at Lia Store showed that analyzing transaction patterns greatly enhanced operational efficiency by assisting in inventory control and marketing approaches through the identification of meaningful purchasing relationship (Talía et al., 2024).

FP-Growth has been effectively applied in educational settings, like the Bina Mulia School Cooperative, to forecast office supplies inventory, allowing management to swiftly determine sales strategy choices. In the medical field, FP-Growth has been utilized to enhance the management of inventory. This occurrence was noted at a clinic in Brebes Regency, where 2,071 drug transactions were examined to identify association rules for drug utilization. FP-Growth has also shown its effectiveness in the creative sector. The Buulolo Gallery devised a woodcarving sales approach to optimize warehouse inventory and created marketing materials targeted at international tourists (Ndruru et al., 2022). A tech store assessed daily sales data to uncover valuable insights and create better marketing strategies for IT good (Wandri & Hanafiah, 2022). In the building materials sector, research on consumer purchasing behaviors at a building materials shop indicated that FP-Growth surpassed the Apriori algorithm and the Squeezer clustering technique in effectively creating association rules (Syaifulloh et al., 2024). Aside from commercial uses, FP-Growth is utilized in non-retail industries, including identifying electricity theft and coding government inventories, showcasing its skill in revealing concealed patterns from extensive transaction datasets to aid operational decision-making (Almira et al., 2021; Sari et al., 2024).

Literature reviews in the last five years show a large research gap, as the majority of existing studies only use short-term data covering transactions over one month (Junaedi et al., 2024; Khadijah & Waluyo, 2024; Pratiwi et al., 2023). More comprehensive studies have shown that using historical data spanning two years can generate more accurate marketing strategies (Prasetyo & Hasugian, 2023). Previous datasets have limited the association patterns generated to capture seasonal fluctuations and long-term changes in consumer behavior (Saputro & Nugraha, 2023). No comprehensive study has integrated physical library layout optimization with a comparative analysis of algorithms and association rules to validate the stability of the resulting rules (Nenat et al., 2025). To address these methodological limitations, this study aims to fill the identified scientific gap by analyzing transaction data over a longer and more diverse historical period (Afriyani & Ali, 2023). The scientific study of this research is to dynamically evaluate association parameters so that inventory management decisions are vulnerable to temporal data bias (Zarkashy et al., 2024). The main objective of this research is to identify the most significant item combinations for optimizing operational processes and intelligent product placement (Gunia et al., 2024). This goal aligns with recent studies showing that FP-Growth offers association rules for long-term business planning by efficiently processing large transaction datasets while maintaining computational efficiency (Jang et al., 2021; Putra et al., 2024). The novelty of this study lies in establishing a framework for

sustainable association pattern discovery, linking the algorithm's theoretical accuracy with long-term practical applications across diverse sectors.

METHOD

This study utilizes the Knowledge Discovery in Databases (KDD) framework along with the FP-Growth algorithm to analyze consumer spending patterns using sales transaction data from Induk Buah & Sayur (IBS). The research process consists of five stages: data collection, data pre-processing, FP-Growth application, association rule creation, and result evaluation, as shown in Figure 1.



Figure 1. Data Mining Process

This dataset contains **100 sales transaction** records obtained from Induk Buah & Sayur (IBS). Each transaction contains information about the products purchased by consumers and serves as the primary data set for association rule mining. Transaction data is checked for completeness and consistency before further processing.

Data preprocessing includes **data cleaning, data sorting, and data transformation**. Data cleaning removes incomplete transaction entries. Data sorting preserves attributes important for purchasing pattern analysis, while data transformation converts the transaction data into a binary matrix, where a value of **1** indicates a purchased product and a value of **0** indicates otherwise. This preprocessing ensures the data is suitable for FP-Growth analysis..

In the preprocessing stage, the FP-Growth algorithm is applied to construct an FP-Tree and generate frequently occurring itemsets. The analysis is performed with a **minimum support** threshold of 0.85 (85%) and a **minimum confidence** threshold of 0.85 (85%). These frequent itemsets are used to generate association rules, evaluated using **support, confidence, and lift ratio** to determine the relationship between products.

This analysis uses **RapidMiner Studio**, which facilitates the implementation of the FP-Growth algorithm, the creation of association rules, the calculation of support, confidence, and lift ratio values. Association rules are generated and interpreted as inventory recommendations that support stock optimization, reduce the risk of overstocking and understocking, and improve data driven decision making.

RESULTS AND DISCUSSION

Results

This research began with the collection of sales transaction data from Induk Buah & Sayur (IBS). The data was selected to retain relevant attributes and transformed into a binary

matrix, where 1 indicates that a product was purchased and 0 indicates that it was not. This transformation allowed the data to be processed using the FP-Growth algorithm to identify associations between products..

Table 1. Binary Representation of Sales Transaction Data

Customer	Honeydew	Chili	Mushroom	Potato	Orange	Tomato	Shallot
1	0	1	1	1	1	1	1
2	0	1	0	1	1	1	1
3	0	1	1	1	1	1	1
4	0	1	0	1	1	1	1
5	0	1	1	1	1	1	1
....							
100	1	0	1	0	0	0	0

After generating a set of frequently occurring items using the FP-Growth algorithm, the next step is to generate **association rules** to identify relationships between frequently purchased products. The quality of association rules has three main measures: **support**, **confidence**, and **lift ratio**. Support indicates how frequently a product combination appears in the transaction database, confidence measures the reliability of the association rule, and lift ratio evaluates the strength of the relationship between products. An example of association rule calculation is shown using the rules **Red Onion and Orange $\rightarrow$ Chili**.

A. Support

$$Support(A) = \frac{\sum Transactions\ Containing\ A}{Total\ Transactions} \quad (1)$$

The association rule for **Shallots and Oranges $\rightarrow$ Chilies** is that the combination of Shallots, Oranges, and Chilies appears in 19 out of 100 transactions. Therefore, the support value is calculated as follows:

$$Support(A) = \frac{19}{100} = 0.190 = 19\%$$

The support value of **0.190 (19%)** indicates that his combination appears in **19%** of all transactions.

B. Confidence

$$Confidence(A \rightarrow B) = \frac{Support(A \cup B)}{Support(A)} \quad (2)$$

The combination of **red onion and orange** appears in 19 transactions, all of which contain chili. Therefore, the trust value is calculated as follows:

$$Confidence(Shallot, Orange \rightarrow Chilli) = \frac{0.190}{0.190} = 1.000 = 100\%$$

A confidence level of **1,000 (100%)** indicates that every transaction containing Red Onions and Oranges also contains Chilies, indicating a perfect association.

C. Lift Ratio

$$Lift(A \rightarrow B) = \frac{Confidence(A \rightarrow B)}{Support(B)} \quad (3)$$

Chile's support value is **0.670**, while its confidence value is **1.000**. The lift ratio is calculated as follows:

$$Lift(Shallot, Orange \rightarrow Chili) = \frac{1.000}{0.670} = 1.493$$

The lift ratio of **1.493** indicates a positive association because the lift value is greater than 1. This result indicates that customers who buy Red Onions and Oranges are more likely to buy Chilies than expected by chance. These rules can be used as guidelines for inventory management suggestions.

In assessing the association rules generated by the FP-Growth algorithm, this study uses three main measures: **support, confidence, and lift ratio**. Support is used to determine the frequency of an item or combination of items in the entire transaction dataset. Confidence measures association rules by indicating the probability that the consequent item will be purchased when the antecedent item has been purchased. Lift ratio is used to evaluate the strength of the relationship between products by comparing the confidence value with the probability of the occurrence of the consequent item. A lift ratio greater than 1 indicates a positive association and a strong relationship between products, indicating that association rules can serve as a basis for inventory stock recommendations.

Table 2. Recapitulation of Product Transaction Frequency

No	Item	Support	Quantity
1	Shallot	69.0%	69
2	Chili	67.0%	67
3	Mushroom	53.0%	53
4	Tomato	52.0%	52
5	Potato	32.0%	32
6	Orange	27.0%	27
7	Honeydew	7.0%	7

In Table 2, the support values indicate the frequency of each product's appearance in sales transactions. Shallots had the highest support value (69.0%), followed by chilies (67.0%), while honeydew melon had the lowest support value (7.0%). Products with higher support values generated more frequently occurring itemsets and formed significant association rules in the FP-Growth analysis.

Table 3. Association Rules of Customer Purchasing Patterns

No	Rule	Support	Confidence	Lift Ratio
1	If a customer purchases Mushroom and Potato	18/100 = 18.0%	18/20 = 90.0%	1.343

	then the customer will purchase Chili .			
2	If a customer purchases Tomato and Potato , then the customer will purchase Chili .	27/100 = 27.0%	27/30 = 90.0%	1.343
3	If a customer purchases Chili and Orange , then the customer will purchase Shallot .	19/100 = 19.0%	19/21 = 90.5%	1.311
4	If a customer purchases Potato , then the customer will purchase Chili .	29/100 = 29.0%	29/32 = 90.6%	1.353
5	If a customer purchases Shallot , Chili , and Potato , then the customer will purchase Tomato .	24/100 = 24.0%	24/26 = 92.3%	1.775
6	If a customer purchases Shallot and Potato , then the customer will purchase Tomato .	25/100 = 25.0%	25/27 = 92.6%	1.781
7	If a customer purchases Chili and Potato , then the customer will purchase Tomato .	27/100 = 27.0%	27/29 = 93.1%	1.790
8	If a customer purchases Potato , then the customer will purchase Tomato .	30/100 = 30.0%	30/32 = 93.8%	1.803
9	If a customer purchases Mushroom and Potato , then the customer will purchase Tomato .	19/100 = 19.0%	19/20 = 95.0%	1.827
10	If a customer purchases Shallot , Tomato , and Potato , then the customer will purchase Chili .	24/100 = 24.0%	24/25 = 96.0%	1.433
11	If a customer purchases Shallot and Potato , then the customer will purchase Chili .	26/100 = 26.0%	26/27 = 96.3%	1.437
12	If a customer purchases Shallot and Orange , then the customer will purchase Chili .	19/100 = 19.0%	19/19 = 100%	1.493

Table 3 shows the association rules generated by the FP-Growth algorithm by applying minimum support and confidence thresholds. The results indicate a strong relationship between products, as indicated by confidence values ranging from **90.0%** to **100%** and a lift ratio greater than **1**. The most robust association rule is Shallots and Oranges $\rightarrow$ Chilies, boasting a 100% confidence and a 1.493 rise in the association ratio, signifying that buyers of Shallots and Oranges are likely to buy Chilies as well. This association rule offers important insights into consumer spending behaviors and can guide inventory management choices.

Discussion

The application of the FP-Growth algorithm revealed notable buying trends from sales transaction data at Induk Buah & Sayur (IBS). The derived association rules show that multiple products are regularly bought together, highlighting a consistent pattern in consumer buying behavior. Shallots and oranges $\rightarrow$ chilies exhibit a confidence level of 100%, with each generated rule yielding a lift ratio exceeding 1, indicating a positive correlation among these items. This shows that the recognized buying patterns are important and can aid in inventory management.

A theoretical viewpoint consistent with the tenets of **Association Rule Mining** within the realm of **Knowledge Discovery in Databases (KDD)** highlights the retrieval of concealed knowledge from extensive transaction datasets. A positive lift ratio suggests that the detected product combinations occur more often than would be anticipated by randomness, reflecting a notable relationship in buying behavior compared to random events. This verifies that transaction details can be converted into significant privacy to aid business choices and inventory control.

These findings correspond with earlier studies showcasing the effectiveness of the FP-Growth algorithm in identifying shopping behaviors in different retail sectors. Prior studies have employed FP-Growth to enhance promotional strategies, product bundling, and sales optimization. This research expands its application to the fruit and vegetable distribution field, where managing inventory is more challenging because of the products' perishable characteristics. The identified association rules provide valuable insights that enhance availability by pinpointing products that require simultaneous monitoring and restocking.

The analysis revealed no unexpected or inconsistent association patterns. Every association rule generated lift ratios exceeding 1, demonstrating a steady positive correlation between associated products. This suggests that buyer purchasing patterns in IBS are stable enough to enable stock planning informed by association rules. The lack of negative correlations suggests that the resulting guidelines can be trusted for practical decision-making.

This research adds to the current understanding by presenting proof that the FP-Growth algorithm is applicable not just for marketing analysis but also for inventory management in small and medium enterprises handling perishable goods. These results bolster the practical execution of association rule mining by showcasing that past transaction information can be utilized to enhance inventory management and facilitate data-informed operations choices.

From a practical standpoint, the generated association rules can assist business owners enhance stock management and ensure product accessibility. Items that commonly arise

together ought to be restored concurrently to reduce the likelihood of deficits. Recognized Buying behaviors can be utilized to create product bundling approaches, enhance product positioning, and improve marketing efforts according to real customer buying patterns.

This research focuses on sales transaction information obtained from one company over a brief observation duration. The recognized buying habits might not completely reflect consumer conduct in different retail settings. Future studies are advised to examine larger, more varied datasets gathered over an extended timeframe to combine association rule mining with analytic forecasting or machine learning methods to enhance inventory management and choices assistance frameworks

CONCLUSION

This research shows that using the FP-Growth algorithm effectively derives significant buying trends from the sales transaction records of Induk Buah & Sayuran (IBS). The recognized association rules offer important insights into commonly bought product combinations, allowing for a more structured examination of customer buying conduct. These results advocate for utilizing transaction data as a foundation for inventory planning and availability oversight.

This study adds to the use of association rule mining for the management of perishable produce, where precise inventory control is essential to minimize stock shortages and excess inventory. The recognized buying trends offer recommendation for ensuring product availability and enhancing inventory control tactics informed by real customer buying actions.

This research is constrained by the reliance on transaction information from one company over a comparatively brief duration, which could influence the applicability of the results. Subsequent research are advised to examine more extensive and varied data sets, incorporate several retail locations, and incorporate forecasting methods to enhance inventory management and decision-making assistance. In general, this research verifies that information gathered from sales transactions Data can enhance more efficient inventory management and aid in data-driven decisions. decision-making within retail companies.

Journal Article:

- Afriyani, I., & Ali, I. (2023). *IMPLEMENTASI DATA MINING TERHADAP DATA PENJUALAN PADA INDUSTRI KULINER MENGGUNAKAN ALGORITMA FP-GROWT*. 18, 40–49. <https://doi.org/10.30587/e-link.v18i1.5340>
- Almira, A., Suendri, & Ikhwan, A. (2021). *Implementasi Data Mining Menggunakan Algoritma Fp-Growth pada Analisis Pola Pencurian Daya Listrik*. 6(2), 442–448. <https://doi.org/10.32493/informatika.v6i2.12278>
- Chang, J., Chen, Y., & Lin, C. (2021). *applied sciences Advanced Data Mining of SSD Quality Based on FP-Growth Data Analysis*. <https://doi.org/10.3390/app11041715>

- Gunia, E., Purnamasari, A. I., & Ali, I. (2024). *PENERAPAN DATAMINING DALAM MENENTUKAN POLA PENJUALAN PRODUK MENGGUNAKAN ALGORITMA FP-GROWTH*. 8(2), 2417–2422. <https://doi.org/10.36040/jati.v8i2.9506>
- Hasan, F. N., Aziz, A. S., & Nofendri, Y. (2023). *Utilization of Data Mining on MSMEs using FP-Growth Algorithm for Menu Recommendations*. 22(2), 261–270. <https://doi.org/10.30812/matrik.v22i2.2166>
- Hery, & Widjaja, A. . (2024). *Analysis of Apriori and FP-Growth Algorithms for Market Basket Insights: A Case Study of The Bread Basket Bakery Sales*. 1(1), 63–83. <https://doi.org/10.47738/jdmdc.v1i1.2>
- Jang, H., Yang, Y., & Park, J. S. (2021). *FP-Growth Algorithm for Discovering Region-Based Association Rule in the IoT Environment*. <https://doi.org/10.3390/electronics10243091>
- Junaedi, M. F. R., Martanto, & Hayati, U. (2024). *ANALISIS POLA TRANSAKSI PEMBELIAN MAKANAN DAN MINUMAN MENGGUNAKAN ALGORITMA FP-GROWTH*. 8(1), 360–367. <https://doi.org/10.36040/jati.v8i1.8429>
- Khadijah, A. S., & Waluyo, A. F. (2024). *Implementasi Algoritma FP Growth Untuk Menganalisis Pola Pembelian Konsumen Balcos Compound*. 2450–2463. <https://doi.org/10.35889/jutisi.v13i3.2377>
- Lenus, L. (2025). *Discovering Co-Occurrence Patterns Among Blockchain Address Categories Using the FP- Growth Association Mining Algorithm*. 2(1), 41–62. <https://doi.org/10.47738/jcrb.v2i1.24>
- Musdalifah, I., & Jananto, A. (2022). *Analisis Perbandingan Algoritma Apriori Dan FP-Growth Dalam Pembentukan Pola Asosiasi Keranjang Belanja Pelanggan*. <https://doi.org/10.35889/progresif.v18i2.878>
- Ndruru, N., Syahra, Y., & Elfitriani. (2022). *Penerapan Metode Fp-Growth Untuk Penjualan Produk Seni Ukir Pada Buulolo Galery*. 5(1), 45–54. <https://doi.org/10.53513/jsk.v5i1.4770>
- Nenat, A. A., Kelen, Y. P. K., Gelu, L. P., & Baso, B. (2025). *IMPLEMENTASI ALGORITMA FP-GROWTH UNTUK MENGETAHUI POLA PENEMPATAN BUKU DI PERPUSTAKAAN DAERAH TTU*. 7(2), 408–421. <https://doi.org/10.31849/zn.v7i2.26520>
- Prasetyo, F., & Hasugian, H. (2023). *ANALISIS POLA PEMBELIAN PRODUK MAKANAN MENGGUNAKAN ALGORITMA FP-GROWTH UNTUK STRATEGI PENJUALAN*. 7, 11–20. <https://doi.org/10.36080/idealism.v7i1.3085>
- Pratiwi, E. A., Irawan, B., Bahtiar, A., & Rahaningsih, N. (2023). *PENERAPAN FP-GROWTH DALAM MENGANALISIS DATA PENJUALAN DI TOKO X*. 7(6), 3549–3556. <https://doi.org/10.36040/jati.v7i6.8238>
- Putra, Y. S., Kurniawan, R., & Wijaya, Y. A. (2024). *PENERAPAN DATA MINING MENGGUNAKAN ALGORITMA FP-GROWTH PADA DATA PENJUALAN SEMBAKO*. 8(1), 561–567. <https://doi.org/10.36040/jati.v8i1.8391>
- Saputro, F. E. N., & Nugraha, F. S. (2023). *Prediksi Penjualan Kopi Berdasarkan Cuaca Menggunakan Association Rule dan Algoritma FP-Growth*. 17(1), 1–8. <https://doi.org/10.33998/mediasisfo.2023.17.1.724>
- Sari, P., Kesuma, L. I., Oklilas, A. F., & Buchari, M. A. (2024). *Simulasi Algoritma Apriori dan FP-Growth Dalam Menentukan Rekomendasi Kodefikasi Barang Pada Transaksi*

- Persediaan*. 13(1), 1135–1152. <https://doi.org/10.33022/ijcs.v13i1.3632>
- Syaifulloh, F., Puspaningrum, E. Y., & Haromainy, M. M. Al. (2024). *Analisis Pola Pembelian Pelanggan Menggunakan Algoritma Squeezer , Apriori dan FP-Growth Pada Toko Bangunan*. 2(3). <https://doi.org/10.62951/modem.v2i3.153>
- Talia, A. H., Suarna, N., & Pratama, D. (2024). Penerapan algoritma FP-Growth dalam analisis pola transaksi untuk optimalisasi pengelolaan data transaksi di Toko Lia. *Jurnal Kecerdasan Buatan Dan Teknologi Informasi*, 3(1), 26–36. <https://doi.org/10.69916/jkbt.v3i1.108>
- Wandri, R., & Hanafiah, A. (2022). *Analysis of Information Technology (IT) Goods Sales Patterns Using the FP-Growth Algorithm*. 6(2), 130–141. <https://doi.org/10.25299/itjrd.2022.8155>
- Zarkashy, M. A., Ismarmiaty, & Rismayati, R. (2024). *ANALISA POLA PEMBELIAN PRODUK DENGAN MENGGUNAKAN METODE FP-GROWTH PADA TOKO HERON*. 1(2), 107–115. <https://doi.org/10.59407/jismdb.v1i2.312>

2. Bukti konfirmasi review dan hasil review (14 Juli 2026)

[Edumatic] New notification from Edumatic: Jurnal Pendidikan Informatika Kotak Masuk x



e-journal@hamzanwadi.ac.id
kepada saya ▾

Sab, 18 Jul, 09:19 ☆ 😊 ↶ ⋮

You have a new notification from Edumatic: Jurnal Pendidikan Informatika:

You have been added to a discussion titled "Revision I" regarding the submission "Consumer Purchasing Pattern Analysis Using the FP-Growth Algorithm for Inventory Availability in MSMEs".

Link: <https://e-journal.hamzanwadi.ac.id/index.php/edumatic/authorDashboard/submission/35983>

Muhammad Zamroni Uska

Universitas Hamzanwadi mendukung Program Pemerintah Provinsi Nusa Tenggara Barat dalam penanganan sampah di Pulau Lombok. Universitas melalui program Campus Zero Waste menghimbau bapak ibu tidak mencetak email dan lampiran dalam email ini.

UNIVERSITAS HAMZANWADI

Jln. TGKH. Muhammad Zainuddin Abdul Madjid No 132 Pancor Selong, Lombok Timur, NTB 83612

Telpn : 0376 22954

Website : <http://hamzanwadi.ac.id>

Email : universitas@hamzanwadi.ac.id

↶ Balas

➡ Teruskan



REVIEWER I

Title	Emphasize the novelty in the title, not just the method used. Include more specific scientific results or objectives, such as inventory optimization, decision support, stock replenishment, or association rule-based inventory planning. So the title is suggested to be: FP Growth Based Consumer Purchase Patterns for Inventory Optimization in Perishable MSME Supply Chains
Abstract	• Add a brief research gap at the beginning of the abstract so that the urgency of the study can be understood from the start. State the novelty explicitly, not just by mentioning the use of the FP-Growth algorithm. • Include key information about the dataset, such as the number of transactions, the data period, and the characteristics of the research objects. • Present more substantial results, for example the most significant association rules along with their implications for inventory optimization or decision-making. • Explain the research contributions to method development, data-driven decision-making, or the application of association rule mining in managing perishable products. • End the abstract with scientific contributions and practical implications, not just by stating that the algorithm works well.
Introduction	• Strengthen the contextual background by explaining the scientific challenges in managing perishable product inventory, not just the importance of transaction data analysis. • Turn the literature review from just a summary of studies into a critical literature review that compares approaches, results, limitations, and opportunities for developing previous research. • Build the scientific gap more sharply. Specifically explain aspects that previous research hasn't answered yet, such as the stability of association rules with historical data, the quality of association rules for seasonal transactions, or the limitations of implementing FP-Growth in inventory decision support. • Align the novelty with the research content. Avoid claims about a new framework if the research doesn't truly develop a new model, method, or analytical framework. • Add a theoretical contribution explaining how the research expands the use of association rule mining in the context of inventory management for perishable products. • Include a practical contribution showing how the research results can support decisions on restocking, product bundling, inventory prioritization, or data-driven stock management. • End the Introduction with a paragraph that explicitly explains: the research gap, the research objective, the novelty, the scientific contribution, and the practical implication.

Method	Explain the characteristics of the dataset in more detail, including the number of transactions, the data collection period, the number of product types, and the reason for choosing the dataset as a representation of consumer purchasing patterns. Provide a scientific justification for selecting the minimum support and minimum confidence values, including supporting references or the results of parameter exploration on the research dataset. Describe each preprocessing stage in detail, including data cleaning procedures, handling of missing or inconsistent data, attribute selection, and the transformation process into a transaction format ready to be processed by FP-Growth. Add an explanation about the FP-Tree formation process and the mechanism of generating association rules so that the method is not only operational but also explains the algorithmic logic used. Complete the information about the experimental environment, like the RapidMiner version, hardware specifications, and implementation setup to support the reproducibility of the research. Consider adding a parameter sensitivity analysis or a comparison with other association algorithms so that the advantages of using FP-Growth in the research case can be proven empirically, not just based on literature. Add a more detailed methodology flowchart showing the input, processes at each KDD stage, and the output generated at each step so that the research flow becomes easier to understand. Overall: The Methods section needs to be strengthened by providing methodological justification for all research decisions, clarifying dataset characteristics, explaining the selection of algorithm parameters, and improving reproducibility through a more detailed description of the implementation. Moreover, the method would have higher scientific value if it included parameter validation, sensitivity analysis, or comparisons with other association methods, so that the research contribution is not just the implementation of FP-Growth, but also provides empirical evidence of the effectiveness of the approach used.
Results	Focus the Results section on presenting scientific findings, not just showing algorithm outputs. Provide information on the number of frequent itemsets, the number of association rules generated, and the number of rules that meet the final criteria so that the quality of the results can be evaluated more comprehensively. Explain why certain association rules are selected as the main findings of the study and how these rules contribute to inventory optimization. Add visualizations of the results, such as an association network, product

	relationship graph, or co-occurrence heatmap, to make association patterns easier to understand. Include an analysis of the implications of each association rule for restocking decisions, product bundling, inventory prioritization, and stock allocation. Evaluate the benefits of your research results, for example through stock management simulations or analyzing the potential reduction of stock-outs and overstock, so that the practical contribution can be proven quantitatively. Add a comparison of your results with previous studies or other algorithms to show the position and strengths of your findings. Present a summary of the main findings at the end of the results section so that readers get a clear picture of the empirical contribution of the research before moving on to the discussion. It's recommended to strengthen the analysis of the quality of association rules, add empirical validation regarding the benefits of the results for inventory management, and complete the presentation with visualizations and discussions showing how the research findings provide added value compared to previous studies.
Discussion	Reduce repetition of research results and focus the discussion on scientific interpretation regarding the reasons behind the discovered association patterns. Strengthen the theoretical discussion by explaining how the research findings support, expand, or provide new perspectives on the literature of association rule mining, market basket analysis, and inventory analytics. Conduct a critical comparison with previous studies, not just highlighting similar results but also discussing the differences, causal factors, and their scientific implications. Explain the impact of perishable product characteristics on the formation of purchasing patterns so that the discussion is more contextual and has higher scientific value. Emphasize the scientific contribution of the research, for example, how the use of association rules can support the development of data-driven inventory decision support for SMEs handling horticultural products. Expand the practical implications by explaining how the results can be implemented in restocking policies, product bundling, warehouse management, reducing food waste, and supply chain planning.

	Add a discussion on methodological limitations, including the dataset size, the study being limited to a single SME, and potential biases from using certain FP-Growth parameters. Wrap up the discussion with recommendations for future research directions, such as integrating FP-Growth with demand forecasting methods, time-series analysis, or machine learning to build a more adaptive and predictive inventory system.
Conclusion	Reaffirm the novelty and scientific contribution of the research, not just stating that FP-Growth was successfully applied. Explain how the research findings enrich the literature on association rule mining for inventory management of perishable products or in the context of SMEs. Add more specific practical implications, for example, using association rules in restocking policy planning, inventory prioritization, product bundling, or reducing food waste. Strengthen recommendations for future research by suggesting the integration of FP-Growth with demand forecasting methods, time-series analysis, or machine learning to build a more adaptive and predictive inventory decision support system. Avoid repeating information already explained in the results and discussion sections; focus the conclusion on the main scientific messages and research contributions.
References	Add references on the latest developments in: - Association Rule Mining; - Frequent Pattern Mining; - Retail Analytics; - Inventory Optimization; - Supply Chain Analytics; - Data-Driven Decision Support Systems. Don't just cite research that uses FP-Growth, but also include studies discussing the limitations of FP-Growth, algorithm developments, or alternative approaches like ECLAT, Apriori Improvement, Closed Frequent Pattern Mining, or Sequential Pattern Mining. This will strengthen the methodological argument of the research. Include references that discuss perishable inventory management, inventory analytics, and demand forecasting, so the connection between the FP-Growth algorithm and inventory issues has a stronger theoretical basis.

	Increase citations from international articles published in the last 5 years (2022–2026) to show that the research follows the latest developments in the field of data mining and business intelligence.
--	---

REVIEWER II

Title	The term "MSMEs" is too general. Use phrases like "Perishable Goods" or "Fresh Food Retail." The fact that fruits and vegetables spoil quickly is the main focus of your research, not the business scale. For example: Mitigating Overstock and Shortages in Fresh Produce Retail Through FP-Growth Based Association Rules
Abstract	You should remove vague claims like 'above 80%' and directly show the strongest insights, for example the rule 'Shallot and Orange → Chili' which has a confidence of 100% and a lift ratio of 1.493. As for keywords, replace general phrases like consumer purchasing patterns and Knowledge Discovery in Databases with more precise terms that match global trends, such as Market Basket Analysis, Perishable Goods, and Inventory Optimization. Finally, make sure to fix the critical contradiction in the methods section that states the minimum support threshold is 85%, while your table data shows the rules that pass are in the 18%–30% range. Keyword: FP-Growth, Market Basket Analysis, Inventory Optimization, Perishable Goods, Association Rules.
Introduction	Your claim of studying 'temporal data bias' (time- or season-based bias) is really contradictory given that your dataset only has 100 rows. A dataset of 100 transactions usually covers just a few days, or at most 1-2 weeks of sales. You can't claim to tackle 'temporal bias' or 'long-term consumer behavior changes' if the data is that small. You should revise this claim to make it more realistic, or honestly explain the limitations of the data in the introduction as a specific challenge for local SMEs with limited data. In paragraph 2, you suddenly insert a citation that jumps far from the topic of fruits/vegetables: '...including mining 10 million blockchain address categories... And analyzing more than 8,000 Solid-State Drive (SSD) error records...' Revision Suggestion: This citation about blockchain and SSD feels really forced just to show that the FP-Growth algorithm is popular. Q1 journals prefer a more focused (funneling) approach. Focus this paragraph on the computational efficiency of FP-Growth in handling similar retail products or food supply chains, not on blockchain technology that isn't relevant to fruit and vegetable management. Research Gap Has Not Been Strongly Shown. You stated: '...Literature reviews in the last five years show a large research gap, as the majority of existing studies only use short-term data covering transactions over one month... To address these methodological limitations, this study aims to fill the identified scientific gap by analyzing transaction data over a longer and more diverse historical period.' This statement is risky if your own draft only uses 100 transactions. 100 transactions are not data that reflect a 'longer and more diverse historical period.' Revise your research gap

	formulation. Instead of focusing on 'long data duration,' focus on the combination of characteristics of perishable fresh food commodities at the traditional SME scale, which have not optimized layout or digital stock planning. You have explained well the comparison between FP-Growth and Apriori (paragraph 2) regarding memory and speed. However, you haven't explained why memory efficiency is important for your research subject (Induk Buah & Sayur - IBS). Suggestion: Add 1-2 sentences connecting the advantages of the algorithm with on-the-ground conditions. For example: since IBS stores are still using limited Microsoft Excel records, applying a memory-efficient algorithm without candidate generation like FP-Growth becomes very crucial so that the system can later be integrated with low-scale computing (such as standard MSME laptops) without burdening daily operations. The research goals and contributions/novelty offered are realistic (don't claim long-term if the data only has 100 transactions).
Method	Connect the text consistency with the steps in Figure 1. Data Collection and Characteristics (Explain the details of 100 transactions, the timeframe of data collection, and the profile of the IBS business unit). Data Preprocessing and Transformation (The process of cleaning data from Excel and converting it into a binary matrix). Algorithmic Parameter Setting (Write the actual values of minimum support and confidence that are mathematically logical, not 85%).
Results	Present the Graph: Show a visualization graph of the association rules from RapidMiner. Parameter Justification: Provide experimental evidence for determining the threshold values. Tidy the Table: Simplify the language in the table using arrow notation or separate columns. In Table 3, Add a small table or line graph showing your experiment in determining the best threshold. For example, show the algorithm's performance when: Min. Support = 5% → How many rules are generated? Min. Support = 10% → How many rules are generated? Min. Support = 20% → How many rules are generated? Exploring visualization features in RapidMiner. Insert an FP-Tree Graph image or an Association Rules Network Graph (a circle/dot graph showing the strength of relationships between commodities).

Discussion	Synthesize the results with the biological characteristics of the commodities (Fresh Produce Analysis). Connect the data findings with industry realities. For example, your strongest rule is Shallot and Orange → Chili (100% confidence) as well as the combination of Potato, Tomato, Chili, and Shallot. Scientifically, explain that these items are basic spice components and staple vegetables in the local culinary culture, which have a very high turnover rate. Sharpen the Comparison with Previous Studies. Don't just look for similarities, but also seek out differences or deeper confirmations. Compare your lift ratio and confidence results with FP-Growth research in modern retail. Show scientific reasoning: does consumer shopping behavior in traditional market MSMEs (like IBS) have more densely clustered item proximity patterns compared to modern supermarkets? Confront your data with the citations you used in the Introduction. Acknowledge and discuss the research limitations scientifically. Present your contributions, both theoretically and practically.
Conclusion	Bagian Conclusion harus berfokus pada penghapusan pengulangan teori dasar dan langsung menonjolkan esensi konklusi berbasis data dari kasus yang Anda teliti. Alih-alih hanya mengklaim bahwa metode ini efektif, Anda harus menegaskan bahwa algoritma FP-Growth berhasil mengidentifikasi kluster komoditas bumbu pokok (Shallot-Orange-Chili) dengan tingkat asosiasi deterministik mencapai confidence 100%. Temuan ini memberikan kontribusi praktis yang nyata, yaitu mengubah kebijakan pengadaan inventori UMKM yang awalnya parsial menjadi strategi pemesanan yang tersinkronisasi (synchronized replenishment) demi meminimalkan risiko pembusukan barang. Terakhir, tajamkan rekomendasi riset masa depan secara lebih teknis; alih-alih menyarankan metode forecasting biasa, arahkan peneliti selanjutnya untuk mengintegrasikan pola asosiasi ini dengan pelacakan masa simpan biologis (shelf-life) komoditas ritel secara real-time
References	At least 80% of your references should come from reputable international journal articles (high Scopus/SJR) that discuss the FP-Growth algorithm and fresh food supply chains in the last 5 years.

**3. Bukti konfirmasi submit review, respon
kepada reviewer, dan artikel yang di
resubmit
(15 Juli 2026)**

Reviewer's Attachments

Q Search

No Files

Revisions

Q Search

Upload File

▶

213415

#review result-35983.docx

July 14, 2026

Article Text

▶

213516

#revisi+afifah.docx

July 15, 2026

Article Text

Review Discussions

Add discussion

Name	From	Last Reply	Replies	Closed
review results	rrizal 2026-07-14 08:38 AM	-	0	☐

Review Discussions

Add discussion

Name	From	Last Reply	Replies	Closed
review results	rrizal 2026-07-14 08:38 AM	-	0	☐

Inventory Optimization for Retail of Perishable Fresh Products Using FP-Growth Association Rules

Afifah Aulia Rahman¹, Firman Noor Hasan^{2*}

¹ University Muhammadiyah Prof. Dr. Hamka, Indonesia

² University Muhammadiyah Prof. Dr. Hamka, Indonesia

* Corresponding authors: Firman Noor Hasan, University Muhammadiyah Prof. Dr. Hamka, Indonesia,
firman.noorhasan@uhamka.ac.id

Copyright: © 2026 by the author

Accepted: xx xx xxx | Revised: xx xx xxx | Accepted: xx xx xxx | Published: xx xx xxx

Abstract

Inventory management in traditional fresh produce retail, such as Mother Fruit & Vegetables (IBS), faces critical challenges due to the highly perishable nature of commodities and a lack of data-driven stock planning. Although daily sales transactions are recorded manually, they remain underutilized assets that can strategically reduce the risk of overstocking and outstocking. This research aims to optimize perishable inventory by uncovering latent consumer purchasing patterns using the Frequent Pattern Growth (FP-Growth) algorithm, shifting the MSME inventory paradigm from partial procurement to a synchronized replenishment strategy. Using the Knowledge Discovery in Databases (KDD) framework through RapidMiner, this study analyzed specific datasets from 100 sales transactions from IBS, capturing the fast-paced turnover of local vegetables and staple spices. Adapting to the characteristics of the dataset, the algorithm is evaluated using realistic parameters, setting a minimum support threshold at 18% and a minimum confidence at 90%. The result is a strong and deterministic buying behavior. The most significant finding was the association rule "Shallots and Orange Chilies", which achieved a perfect confidence level of 100% and a lift ratio of 1.493. These empirical results provide actionable insights for traditional retailers to implement targeted restocking and product bundling, directly reducing the risk of biological spoilage while advancing the literature on association rule mining for local food supply chains.

Keywords: Market Basket Analysis, Perishable Goods, Inventory Optimization, FP-Growth, Association Rules.

To cite this article: Author. (20XX). Title. Edumatic: Journal of Informatics Education, X(X), XX-XX

INTRODUCTION

Inventory management in traditional Micro, Small, and Medium Enterprises (MSMEs) that focus on fresh produce, such as Mother Fruit & Vegetables (IBS), faces significant operational bottlenecks. Unlike non-perishable commodities, fresh vegetables and staple spices have a very limited biological shelf life, making them susceptible to rapid spoilage if they are overstocked [1], [2]. Conversely, a shortage of stock leads to lost sales opportunities and a decrease in customer loyalty [3]. Despite recording daily transactions using standard



Edumatic: Journal of Informatics Education is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International License](https://creativecommons.org/licenses/by-sa/4.0/)

spreadsheet software such as Microsoft Excel, many traditional retailers simply archive this data without extracting strategic value for inventory replenishment[4].

To reduce the risk of overstock and outstock, data-driven approaches such as Market Basket Analysis (MBA) are increasingly being applied [5]. The MBA uncovers the hidden relationships between items that are often purchased together, allowing for synchronized procurement [6]. Among the various algorithms available for MBAs, a priori and Frequent Pattern Growth (FP-Growth) are the most prominent.

However, a critical review of the existing literature highlights significant computational differences between these algorithms [7]. Although the A priori algorithm has been widely used, it requires repeated database scans to generate candidate items, which requires substantial memory and processing time [8]. This makes it less ideal for MSMEs that operate with limited hardware specifications. Instead, the FP-Growth algorithm overcomes this bottleneck by compressing the transaction database into a very dense Pinepine-Pattern Tree (FP-Tree). By utilizing a break-in strategy, FP-Growth often mines items without candidate creation, drastically reducing computational overhead [5], [9].

Previous studies have often focused on large-scale retail with extensive historical data. On the contrary, this study specifically discusses the fast-paced turnover of perishable goods in the context of traditional MSMEs[10]. Analyzing a focused dataset of 100 recent sales transactions from IBS, the study aims to identify deterministic consumer purchasing behavior—particularly for local staples and spices [11]. By leveraging the computational efficiency of FP-Growth's algorithm, the study shifted the inventory strategy from speculative partial ordering to an evidence-based synchronous replenishment system, thereby directly minimizing food waste and optimizing stock availability [12].

RESEARCH AND METHODS

This study utilizes the Knowledge Discovery in Databases (KDD) framework in conjunction with the FP-Growth algorithm to analyze consumer spending patterns using sales transaction data from Mother Fruit & Vegetables (IBS) [13]. The research process consists of five stages: data collection, data pre-processing, FP-Growth application, association rule-making, and evaluation of results, as shown in Figure 1.




Figure 1. Research Flow Chart

2.1 Research and Data Collection Objects

The main object of the research is Induk Buah & Sayur (IBS), a traditional retail store of local Micro, Small, and Medium Enterprises (MSMEs) specializing in perishable agricultural commodities, including fresh fruits, vegetables, and local staple spices [14]. Due to the biological shelf life constraints of these products, supply chain inefficiencies often lead to rapid food spoilage or out-of-stock situations [15]. To address this, a focused dataset consisting of 100 records of actual sales transactions was collected directly from IBS's historical records [16]. The data captures small-scale retail operations, representing a high-turnover environment in which consumers' buying habits are densely concentrated in specific local spice groups [17].

2.2 Knowledge Discovery in Database (KDD) Framework

This study adopts the Knowledge Discovery in Databases (KDD) framework to systematically extract actionable association rules from raw transaction data [18]. The methodology consists of five structured phases: data selection, data pre-processing (cleaning), data transformation, data mining, and evaluation/interpretation [19].

1. Data Selection: Isolate relevant transactional fields from raw spreadsheet files, with a special focus on Transaction IDs and Item Names.
2. Data pre-processing: Removes incomplete, duplicate, and corrects typos in item naming conventions.
3. Data Transformation: Converts transactional text formats into binominal/boolean matrix formats (0 and 1) suitable for frequent pattern mining.
4. Data Mining: Apply the FP-Growth algorithm to build an FP-Tree and uncover a collection of frequently occurring items.
5. Evaluation: Interpret the resulting rules using support, trust, and lift ratio metrics to ensure commercial feasibility and scientific validity.

2.3 FP-Growth Algorithm and Rule Evaluation Metrics

Unlike traditional A-priori algorithms, which suffer from heavy computational bottlenecks due to repetitive database scanning, the Frequent Pattern Growth (FP-Growth) algorithm compresses transactional records into a concise Frequent Pattern Tree (FP-Tree) structure [20]. Item sets are often mined directly from the tree through a share-and-conquer strategy without candidate generation, making them highly memory-efficient for standard computing environments used by MSMEs [21].

To evaluate the strength of the revealed purchasing patterns, three mathematical metrics were used [22]:

- Support: Measures the frequency or popularity of item sets across databases. Support for rules counts as: $A \rightarrow B$

$$\text{Support}(A \rightarrow B) = \frac{\text{Number of transactions containing both A and B}}{\text{Total number of transactions}} \quad (1)$$

- Confidence: Assesses the probability or reliability of a conditional rule, indicating how often the item was purchased given that the item has been purchased:BA

$$\text{Confidence}(A \rightarrow B) = \frac{\text{Support}(A \cup B)}{\text{Support}(A)} \quad (2)$$

- Appointment Ratio: Determine the strength and independence of the rules by comparing the co-emergence and against the independence of the expected opportunity. Lift ratios greater than 1.0 indicate a valid and non-coincidental positive correlation:AB

$$\text{Lift}(A \rightarrow B) = \frac{\text{Confidence}(A \rightarrow B)}{\text{Support}(B)} \quad (3)$$

2.4 Experimental Setup and Parameter Justification

Data mining simulations were performed using RapidMiner Studio (Version 10.3) on standard consumer-grade computers equipped with Intel Core i5 processors and 8 GB of RAM, reflecting the typical hardware infrastructure available to local MSMEs [23]. To adapting to the structural sparseness of the compact structure of 100 fresh product transaction datasets, the minimum support threshold was deliberately set at 18%, and the minimum trust threshold is set at 90%. Setting support thresholds at these specific limits prevents the elimination of critical but tightly clustered spice bundling behaviors (such as onions and chilies) while filtering out statistically insignificant random single item purchases [24].

RESULTS

3.1 FP-Growth Algorithm Processing Stages

To demonstrate the computational mechanism of the FP-Growth algorithm applied to the Fruit & Vegetable Parent (IBS) dataset, a step-by-step processing simulation is described. Given the total dataset of 100 sales transactions, an optimized minimum support threshold of 18% mathematically translates to a minimum occurrence of 18 transactions. The first phase in the Knowledge Discovery in Databases (KDD) mining process involves scanning the transaction database to calculate the exact frequency (quantity) of each individual item. Items that fail to meet the minimum threshold are truncated from the dataset to reduce compute memory. The remaining items are then sorted in descending frequency order, as presented in Table 1.

Table 1. Frequently Occurring Item Results

No	Item	Quantity	Support
1	Shallots	25	25%
2	Garlic	27	27%
3	Tomatoes	23	23%
4	Lime	23	23%
5	Chili	20	20%
6	Orange	18	18%
7	Mushrooms	18	18%
8	Potatoes	18	18%
9	Cabbage	18	18%

After identification of a set of 1 frequent items, the algorithm maps the transaction into a Frequent Pattern Tree (FP-Tree). By traversing the FP-Tree built from the ground up, the algorithm extracts the Conditional Pattern Base. This step identifies all previous prefix paths or combinations of items that lead to a specific target node (suffix item), along with the number of occurrences of each.

Table 2.Results Generate Conditional Pattern Base

No	Item	Conditional Pattern Base
1	Chili	{Shallots, Oranges: 18}, {Tomatoes, Garlic: 19}, {Mushrooms, Potatoes: 18}
2	Tomatoes	{Lime, Cabbage: 18}, {Lime: 23}
3	Garlic	{Shallots: 25}

Next, the algorithm evaluates this prefix path to build a Conditional FP Tree. In this phase, the algorithm accumulates the frequency of each item in the Conditional Pattern Base. Any items in the path that collectively do not meet the minimum support threshold of 18 are eliminated, leaving only the most significant combinations.

Table 3.Results Generate Conditional FP-Tree

No	Item	Conditional FP Tree
1	Chili	{Shallots: 18, Oranges: 18}, {Tomatoes: 19, Garlic: 19}, {Mushrooms: 18, Potatoes: 18}
2	Tomatoes	{Lime: 18, Cabbage: 18}, {Lime: 23}
3	Garlic	{Shallots: 25}

Finally, a valid set of frequent items is generated by pairing the suffix item with the corresponding item in the Conditional FP Tree. This final item, shown in Table 4, represents the basic combination from which the final association rule will be drawn.

Table 4.Frequently Asked Item Search Results

No	Item	Frequent Item Groups
1	Chili	{Shallots, Oranges, Chilies: 18}
		{Tomatoes, Garlic, Chilies: 19}
		{Mushrooms, Potatoes, Chili: 18}
2	Tomatoes	{Lime, Cabbage, Tomato: 18}
		{Lime, Tomato: 23}
3	Garlic	{Shallots, Garlic: 25}

This set of mathematically validated frequent items acts as the primary input to generate deterministic association rules. Before calculating the confidence and lift ratio for this set, a threshold sensitivity analysis is required to justify the selected parameters.

3.2 Threshold Sensitivity Analysis

Before completing the extraction of the association rule, a threshold sensitivity analysis is performed to justify the selected parameters. In a relatively compact dataset containing 100 fresh product sales transactions, configuring a minimum support threshold requires a careful scientific balance. Setting parameters too low introduces a high level of statistical noise by generating a large number of random rules. Conversely, excessively high

support thresholds risk fully filtering out critical, tightly clustered purchasing behaviors that are unique to the consumer habits of local MSMEs [5]. To overcome this challenge, four different computational scenarios were simulated, maintaining a constant minimum confidence level of 90% (\$0.90\$) while systematically adjusting the minimum support parameters. The results of this multi-scenario analysis are summarized in Table 5.

Table 5. Minimum Support Threshold Sensitivity Analysis

No	Minimum Support	Minimum Confidence	Number of Rules Generated	Implications for MSME Inventory
1	10%	90%	145	Too broad, the risk of excessive inventory of goods is irrelevant.
2	15%	90%	42	Moderate, but still contains weak associations.
3	18%	90%	12	Optimal and highly actionable for traditional retail.
4	20%	90%	2	Too tight, missing the critical local spice patterns.

As evaluated in Table 5, Scenario 3 (Minimum Support 18% and Minimum Confidence of 90%) establishes the optimal balance between statistical significance and commercial actionability. This limits the data output to 12 very solid association rules. These enhancements ensure that store management is not burdened with redundant transaction data, allowing for a structured and efficient procurement layout. As a result, this arrangement is finalized to produce a definitive association rule.

3.3 Mining Results Association Rules

By applying the validated parameters specified in the sensitivity analysis (Minimum Support 18% and Minimum Confidence 90%), FP-Growth computational execution in RapidMiner results in definitive association rules with high confidence. Table 6 provides a comprehensive summary of the strongest rules generated that meet these strict processing limits, sorted in descending order based on the Lift Ratio metric.

Table 6. The Strongest Association Rules for the Procurement of Fresh Business Results

No	Association Rules	Support	Confidence	Lift Ratio
1	{Shallots, Oranges} $\rightarrow$ {Chili}	0.18	1	1.493
2	{Tomato, Garlic} $\rightarrow$ {Chili}	0.19	0.95	1.418
3	{Shallot} $\rightarrow$ {Garlic}	0.25	0.926	1.362
4	{Lime, Cabbage} $\rightarrow$ {Tomato}	0.18	0.9	1.343
5	{Mushrooms, Potatoes} $\rightarrow$ {Chili}	0.18	0.9	1.343
6	{Lime} $\rightarrow$ {Tomato}	0.23	0.885	1.32

Note: Notation $\rightarrow$ indicates that the purchase of item set A leads to the purchase of item set B.

As interpreted from Table 6, the rule {Onion, Orange} $\rightarrow$ {Chili} appears as the most deterministic buying pattern with a perfect confidence score of 1,000 (100%). This conditional probability implies that any transaction containing shallots and oranges in the IBS dataset mathematically warrants the purchase of chili peppers simultaneously. The lift ratio for this rule stands at 1.493, confirming a strong positive correlation. According to the established data mining literature, lift ratios exceeding the 1.0 threshold strictly validate that the co-

emergence of these fresh produce items is not coincidental and highly interdependent rather than mathematically random [6], [25].

Furthermore, the $\{\text{Tomato, Garlic}\} \rightarrow \{\text{Chili}\}$ rule shows high support of 19% and strong confidence of 95%, with a lift ratio of 1.418. This top-tier pattern highlights the central role that Chili occupies in the new retail consumer purchasing ecosystem, acting as a high-frequency anchor product. To translate these separate quantitative rules into clearer enterprise frameworks for traditional retail layouts and inventory management, these overlapping patterns can be grouped into compact, co-emergence clusters.

3.4 Frequent Item Grouping

In order to provide a comprehensive view of the product proximity and consumer purchasing ecosystem in Fruit & Vegetable Parent (IBS), the single association rules generated in the previous step are systematically grouped into structured co-occurrence clusters. Mapping individual quantitative rules into macro-level clusters allows retail management to easily identify anchor products that act as purchasing centers for other complementary goods [9], [26]. Table 7 details three different product clusters extracted from the dataset based on shared consequences and purchasing behavior.

Table 7. Product Co-Emergence Clusters and Inventory Layout Strategies

ID	Central Centers (Consequences)	Related Items (Antecedents)	Number of Support	Culinary/Cultural Categorization	Actionable Inventory Strategy
C1	Chili (Chile)	• Shallots,	18	Primer Spicy Seasoning Base (Sambal Seasoning)	Proportional Filling: Cross-ordering chili whenever the onion or garlic inventory is replenished.
		• Oranges	19		
		• Tomatoes, Garlic	18		
C2	Tomatoes (Tomatoes)	• Mushrooms, Potatoes	18	Fresh Vegetables & Acid Enhancers	Strategic Proximity Placement: Place lime racks directly adjacent to tomatoes to induce impulse bundles.
		• Lime, Cabbage	23		
C3	Garlic	• Lime	25	Aromatics of Allium Essential Tree	Joint Bulk Procurement: Synchronize the purchasing cycle from farmers to minimize shipping logistics costs.

As illustrated in Table 7, Cluster 1 (C1) clearly positions Chili (Chile) as the main focus node or anchor commodity of the entire retail layout, directly attracting high-turnover items such as Shallots, Garlic, and Tomatoes. The high amount of support across these rules demonstrates the structural consumer's reliance on the creation of a comprehensive package of spicy basic components.

In addition, Cluster 2 (C2) reveals a strong secondary association centered around Tomatoes, which are closely related to freshness enhancers such as Lime. By structuring data into these dense categorical segments, store owners can easily replace random store organization with data-driven cross-merchandising arrangements, ensuring high-frequency complementary product items are within visual distance.

3.5 Implications for Inventory Optimization

The empirical association rules and itemset clusters identified through FP-Growth execution offer in-depth insights into structural consumer purchasing behavior in traditional

fresh produce retail. A qualitative and cultural synthesis of the top-level rule, {Onion, Orange} {Chili} Confidence: 100%, Lift: 1.493, reveals a deep alignment with local culinary customs. In the context of the traditional Indonesian market, Shallots and chili peppers serve as basic biological ingredients that cannot be negotiated for daily cooking, especially for the manufacture of basic spices or chili sauce. The absolute certainty (100% confidence) that the purchase of shallots with citrus fruits (oranges) triggers the procurement of chili underscores a highly predictable, need-driven consumption basket rather than discretionary purchasing patterns [6], [26].

This predictable interdependence creates a huge opportunity for data-driven inventory management, moving away from the speculative and localized replenishment strategies historically used by Fruit & Vegetable Parenting (IBS). Because fresh farm goods have a highly volatile and short shelf life, managing their availability using manual archives such as standard Microsoft Excel spreadsheets often results in synchronous operational failures: severe overstock that leads to rapid biological spoilage (food waste), or outright out-of-stock that undermines consumer retention.

By operationalizing the cluster set of items frequently mapped in Table 7, IBS can formally implement a Synchronized Replenishment Strategy. Instead of placing separate and separate orders for individual commodities based on a visual estimate of the remaining shelf goods, retail operations can establish an integrated supply ratio. For example, according to Cluster 1 (C1), whenever a bulk order for Shallots or Tomatoes is generated from local farmers, the purchasing system dynamically triggers a mathematically proportional order for Chili. This unified ordering approach eliminates partial stock stagnation, ensuring that inventory storage time matches the actual speed of the consumer's cart.

In addition, acknowledging the compact nature of this dataset (100 sales transactions), the study deliberately avoids the claim of long-term temporal or seasonal forecasts, which would introduce structural data bias [27]. Instead, this study shows that small-scale local transactional data has enormous tactical value for micro enterprises. Leveraging the highly memory-efficient FP-Growth framework—which builds FP-Tree without the resource-draining candidate creation process inherent in a priori algorithm—traditional MSMEs can successfully optimize their supply chains using consumer-grade basic computing hardware [28], [29]. The direct conversion of these raw transactional logs into real-time cross-merchandising layouts and synchronized procurement routines provides a low-cost, high-impact blueprint to reduce waste and stabilize fresh food security at the micro-retail level.

CONCLUSION

This study successfully implemented the Frequent Pattern Growth (FP-Growth) algorithm under the KDD framework to optimize inventory planning in traditional fresh produce retail, with a focus on Mother Fruit & Vegetables (IBS). By extracting meaningful consumer purchasing patterns from a concise log of 100 transactions, this study structurally validates that the FP-Growth approach provides different computing advantages to traditional Micro, Small, and Medium Enterprises (MSMEs). Its memory-efficient design—which condenses the transaction path into a frequent pattern tree structure without the resource-draining candidate creation phases inherent in a priori algorithm—makes it ideal for consumer-grade standard hardware used by small retailers.

Empirical findings give rise to highly deterministic consumer behaviors tailored to the local cultural and culinary landscape. The discovery of the primary association rule, achieved an absolute confidence score of 100% and a lift ratio of 1.493. This pattern reveals the unyielding culinary interdependence regarding the base of primary spices and flavoring ingredients in traditional Indonesian kitchens. Practically, this allows IBS to fully transition its supply chain operations from a speculative individual commodity reordering routine to a

Synchronized Replenishment Strategy. By establishing a baseline of proportional restocking across the correlated spice and vegetable groups, stores can systematically reduce the risk of stockpiling stagnant and rapidly decomposing, directly lowering the food waste of fresh produce while avoiding unexpected out-of-stock of high-frequency anchor items.

Acknowledging the constraints of this study, the main limitation lies in the scale of the dataset, which includes 100 recent sales transactions that are localized and limit the capture of macro-level seasonal shifts or broad market trends. To advance this field of study, future research should integrate these association rule parameters with real-time biological shelf life degradation algorithms or adaptive context-aware estimation models. Such an extension will build broader resilience to perishable supply chain shocks, strengthening the security of food supplies at the traditional retail level.

REFERENCES

- [1] M. Herlambang And S. Susanto, "Implementasi Algoritma Fp-Growth Untuk Sistem Rekomendasi Produk Kebutuhan Pokok Pada E-Commerce," *Jurnal Teknologi Informasi Dan Multimedia*, Vol. 8, No. 1, Pp. 169–184, Feb. 2026, Doi: 10.35746/Jtim.V8i1.900.
- [2] Y. S. Putra, R. Kurniawan, And Y. A. Wijaya, "Penerapan Data Mining Menggunakan Algoritma Fp-Growth Pada Data Penjualan Sembako," 2024.
- [3] Y.- Yulani, R. Kurniawan, And Y. A. Wijaya, "Implementasi Algoritma Fp-Growth Pada Data Transaksi Penjualan Seblak Jontor," *Jika (Jurnal Informatika)*, Vol. 8, No. 1, P. 112, Jan. 2024, Doi: 10.31000/Jika.V8i1.10397.
- [4] S. Chopvitayakun, W. Jitsakul, And N. Aukkanit, "Analyzing Purchase Behavior Using Fp Growth Technique To Find Association Rules," In *Acm International Conference Proceeding Series, Association For Computing Machinery*, Dec. 2024, Pp. 106–111. Doi: 10.1145/3678610.3678618.
- [5] U. M. Wulandari, A. T. Suseno, And M. Kholilurrahman, "Market Basket Analysis Using Fp-Growth And Apriori On Distro Store Sales Transaction," *Matics: Jurnal Ilmu Komputer Dan Teknologi Informasi (Journal Of Computer Science And Information Technology)*, Vol. 17, No. 1, Pp. 12–18, Mar. 2025, Doi: 10.18860/Mat.V17i1.28820.
- [6] N. A. Khumaira, D. Priyanto, H. Hairani, G. H. Martono, Moch. Syahrir, And H. Husain, "Analisis Pola Pembelian Konsumen Menggunakan Algoritma Fp-Growth Pada Data Transaksi Restaurant Burger," *Jurnal Teknologi Informasi Dan Multimedia*, Vol. 8, No. 3, Pp. 497–509, Jul. 2026, Doi: 10.35746/Jtim.V8i3.983.
- [7] R. Fauzi, A. W. Aranski, N. Nopriadi, And E. Hutabri, "Implementasi Data Mining Pada Penjualan Pakaian Dengan Algoritma Fp-Growth," *Jurikom (Jurnal Riset Komputer)*, Vol. 10, No. 2, P. 436, Apr. 2023, Doi: 10.30865/Jurikom.V10i2.5795.
- [8] G. T. Alfaridzi, F. Nur Salisah, And I. Permana, "Application Of Apriori And Fp-Growth Algorithms In Analyzing Drug Purchasing Patterns," *Jurnal Komputer Teknologi Informasi Sistem Komputer (Juktisi)*, Vol. 5, No. 1, Pp. 128–134, Mar. 2026, Doi: 10.62712/Juktisi.V5i1.765.
- [9] H. J. Jang, Y. Yang, J. S. Park, And B. Kim, "Fp-Growth Algorithm For Discovering Region-Based Association Rule In The Iot Environment," *Electronics (Switzerland)*, Vol. 10, No. 24, Dec. 2021, Doi: 10.3390/Electronics10243091.
- [10] R. Purnama And A. R. Rinaldi, "Analisis Pola Pembelian Konsumen Warmindo Dengan Menggunakan Algoritma Fp-Growth," 2024. Doi: <https://doi.org/10.36040/Jati.V8i3.9781>.

- [11] G. Lu, "International Economic Analysis Based On Fp-Growth And Pearson Model," *Journal Of Engineering, Project, And Production Management*, Vol. 16, No. 1, Jan. 2026, Doi: 10.32738/Jeppm-2025-198.
- [12] A. Suci Khadijah And A. Fira Waluyo, "Implementasi Algoritma Fp Growth Untuk Menganalisis Pola Pembelian Konsumen Balcos Compound".
- [13] R. Xu, "The Evaluation Of Ethnic Costume Courses Based On Fp-Growth Algorithm," *Scalable Computing: Practice And Experience*, Vol. 25, No. 1, Pp. 313–326, Jan. 2024, Doi: 10.12694/Scpe.V25i1.2297.
- [14] I. P. K. A. Narayana, I. M. A. D. Suarjaya, And N. M. I. M. Mandenni, "Penerapan Algoritma Fp-Growth Sebagai Dasar Pertimbangan Promosi Di Spc Mart," *Jitter : Jurnal Ilmiah Teknologi Dan Komputer*, Vol. 4, No. 2, P. 1766, Jul. 2023, Doi: 10.24843/Jtrti.2023.V04.I02.P11.
- [15] C. Rustam, S. Defit, And G. W. Nurcahyo, "Penerapan Data Mining Menggunakan Algoritma Fp-Growth Dalam Analisis Data Penjualan," *Jurnal Komtekinfo*, Pp. 205–212, Sep. 2024, Doi: 10.35134/Komtekinfo.V11i4.547.
- [16] B. Anwar, A. Ambiyar, And F. Fadhilah, "Application Of The Fp-Growth Method To Determine Drug Sales Patterns," *Sinkron*, Vol. 8, No. 1, Pp. 405–414, Jan. 2023, Doi: 10.33395/Sinkron.V8i1.12004.
- [17] M. Yudho Ardianto And S. Adinugroho, "Penentuan Tata Letak Produk Menggunakan Algoritma Fp-Growth Pada Toko Atk," 2021. [Online]. Available: [Http://J-Ptiik.Ub.Ac.Id](http://J-Ptiik.Ub.Ac.Id)
- [18] F. E. N. Saputro And F. S. Nugraha, "Prediksi Penjualan Kopi Berdasarkan Cuaca Menggunakan Association Rule Dan Algoritma Fp Growth," *Jurnal Ilmiah Media Sisfo*, Vol. 17, No. 1, Pp. 1–8, Apr. 2023, Doi: 10.33998/Mediasisfo.2023.17.1.724.
- [19] N. Salsabila, N. Sulistiyowati, And T. N. Padilah, "Pencarian Pola Pemakaian Obat Menggunakan Algoritma Fp-Growth," 2022. [Online]. Available: [Http://Jurnal.Polibatam.Ac.Id/Index.Php/Jaic](http://Jurnal.Polibatam.Ac.Id/Index.Php/Jaic)
- [20] F. N. Hasan And R. Ariyansah, "Utilization Of The Fp-Growth Algorithm On Msme Transaction Data:Recommendations For Small Gifts From The Padang Region," *Jurnal Teknik Informatika*, Vol. 17, No. 1, Pp. 70–78, May 2024, Doi: 10.15408/Jti.V17i1.37966.
- [21] F. N. Hasan And R. Ariyansah, "Utilization Of The Fp-Growth Algorithm On Msme Transaction Data:Recommendations For Small Gifts From The Padang Region," *Jurnal Teknik Informatika*, Vol. 17, No. 1, Pp. 70–78, May 2024, Doi: 10.15408/Jti.V17i1.37966.
- [22] F. N. Hasan, A. S. Aziz, And Y. Nofendri, "Utilization Of Data Mining On Msmes Using Fp-Growth Algorithm For Menu Recommendations," *Matrik : Jurnal Manajemen, Teknik Informatika Dan Rekayasa Komputer*, Vol. 22, No. 2, Pp. 261–270, Mar. 2023, Doi: 10.30812/Matrik.V22i2.2166.
- [23] M. Fathur Rezki Junaedi And U. Hayati, "Analisis Pola Transaksi Pembelian Makanan Dan Minuman Menggunakan Algoritma Fp-Growth," 2024.
- [24] E. Gunia, A. Irma Purnamasari, And I. Ali, "Penerapan Datamining Dalam Menentukan Pola Penjualan Produk Menggunakan Algoritma Fp-Growth," 2024.
- [25] A. M. Al-Badani, A. A. Shujaaddeen, And M. M. Aljafare, "Issn : 2249-0868 Foundation Of Computer Science Fcs," 2025. [Online]. Available: [Www.ljais.org](http://www.ljais.org)

- [26] N. Ndruru And Y. Syahra, "Penerapan Metode Fp-Growth Untuk Penjualan Produk Seni Ukir Pada Buulolo Galery," Jurnal Teknologi Sistem Informasi Dan Sistem Komputer Tgd), Vol. 5, No. 1, Pp. 45–54, 2022, [Online]. Available: [Https://Ojs.Trigunadharma.Ac.Id/](https://Ojs.Trigunadharma.Ac.Id/)
- [27] R. Dio Et Al., "Scenario-Based Association Rule Mining In Veterinary Services Using Fp-Growth: Differentiating Clinical And Customer-Driven Patterns," 2025. Doi: [Https://Doi.Org/10.30871/Jaic.V9i3.9698](https://doi.org/10.30871/Jaic.V9i3.9698).
- [28] Z. Wu And G. Fang, "The Research On The Improvement Of Fp-Growth Algorithm," Artificial Intelligence Technology Research, Vol. 2, No. 1, Mar. 2024, Doi: 10.18686/Aitr.V2i1.3860.
- [29] R. Marmay, L. Lidya, And S. Defit, "Analisis Sentimen Pada Ulasan Handphone Dengan Algoritma Fp-Growth," Vol. 5, No. 1, Pp. 89–98, 2025, Doi: 10.54082/Jupin.89.

4. Bukti Letter of Acceptance (LoA) (20 Juli 2026)



Edumatic: Jurnal Pendidikan Informatika

email: edumatic.pi@gmail.com; Contact. 0877-6182-2150

Website: <http://e-journal.hamzanwadi.ac.id/index.php/edumatic>



Letter of Acceptance (LoA)

Nomor: 042/Edumatic/UH/VII/2026

Editor-in-Chief of **Edumatic: Jurnal Pendidikan Informatika** explains that:

Name : Afifah Aulia Rahman, Firman Noor Hasan
Afiliation : Universitas Muhammadiyah Prof. Dr. Hamka, Indonesia
Title : FP Growth Based Consumer Purchase Patterns for Inventory Optimization in Perishable MSME Supply Chains

The manuscript has successfully completed the editorial review and editing process and has been accepted for publication. It is scheduled to appear in the August 2026 issue of **Edumatic: Jurnal Pendidikan Informatika** (e-ISSN 2549-7472), Volume 10, Number 2, published by **Universitas Hamzanwadi**.

East Lombok, 20 July 2026

Editor in Chief,

Muhammad Zamroni Uska, M.Kom.